

10 kVA - 75 kVA GENSETS

Technical Specifications:

Genset Rating (kVA)	10	12.5	15	18.5	20	22.5
Duty (Standby/ Prime)	Prime	Prime	Prime	Prime	Prime	Prime
Power Rating (kW)	8	12	12	16	16	18
No. of Phases	1 phase /3 phase	1 phase /3 phase	1 phase /3 phase	1 phase /3 phase	1 phase /3 phase	1 phase /3 phase
Output Voltage (V)	230V/415V	230V/415V	230V/415V	230V/415V	230V/415V	230V/415V
Power Factor (lagging)	0.8	0.8	0.8	0.8	0.8	0.8
Current (A) (1phase / 3 phase)	43/14	54/17	65/21	80/26	84/31	98/31
Frequency (Hz) RPM	50/1500	50/1500	50/1500	50/1500	50/1500	50/1500
Governing Class	Electronic					
Starting system	12V DC Electrical	12V DC Electrical	12V DC Electrical	12V DC Electrical	12V DC Electrical	12V DC Electrical
Fuel tank capacity (lit)	55	55	55	75	75	75
Genset dimensions approx (L x W x H) (mm)	1800 x 900 x 1300	1800 x 900 x 1300	1800 x 900 x 1300	2000 x 980 x 1285	2000 x 980 x 1285	2000 x 980 x 1285
Genset weight (kg)	650	690	740	800	800	840
Engine Specifications						
Make	Mahindra					
Model	2185 GM C2	2205 GM C2	3255 GM C2	3285 GM C2	3305 GM	3335 TCGM C2
Rated Power at 100% Load (HP)	16.3	18.2	22.7	25.4	30	29.9
Aspiration	NA	NA	NA	NA	NA	TC
No. of cylinders	2	2	3	3	3	3
Bore x Stroke (mm)	89 x 110	89 x 120	89 x 102	89 x 110	88.9 x 102	89 x 102
Displacement (cc)	1365	1490	1892	2048	2058	1892
Lube oil specification	SAE15W40 CI4					
Total lube oil system capacity (liter)	6	6	6.5	6.5	6.5	7
Lube oil consumption (lit/hr) ⁵	0.15% of Fuel Consumption					
Lube oil change period (hrs.)	300 hrs. (Oil Change)					
Radiator coolant capacity (liters)	5.5	5.5	5.5	5.5	7.5	5.5
Alternator Specifications						
Make	Leroy Somer					
Enclosure Type	IP23	IP23	IP23	IP23	IP23	IP23
Voltage regulation	±1%	±1%	±1%	±1%	±1%	±1%
Class of insulation	Class H	Class H	Class H	Class H	Class H	Class H
Maximum Unbalanced Load across Phases	25%	25%	25%	25%	25%	25%



10 kVA - 75 kVA GENSETS

Technical Specifications:

Genset Rating (kVA)	25	30	40	50	62.5	75
Duty (Standby/ Prime)	Prime	Prime	Prime	Prime	Prime	Prime
Power Rating (KW)	20	24	32	40	50	60
No. of Phases	1 phase /3 phase	1 phase /3 phase	1 phase /3 phase	3 phase	3 phase	3 phase
Output Voltage (V)	230V/415V	230V/415V	230V/415V	415V	415V	415V
Power Factor (lagging)	0.8	0.8	0.8	0.8	0.8	0.8
Current (A) (1phase / 3 phase)	109/35	130/42	174/56	70	87	104
Frequency (Hz) RPM	50/1500	50/1500	50/1500	50/1500	50/1500	50/1500
Governing Class	Electronic					
Starting system	12V DC Electrical	12V DC Electrical	12V DC Electrical	12V DC Electrical	12V DC Electrical	12V DC Electrical
Fuel tank capacity (lit)	75	115	115	200	200	230
Genset dimensions approx (L x W x H) (mm)	2000 x 980 x 1285	2500 x 1030 x 1330	2500 x 1030 x 1330*	2800 x 1150 x 1535*	2800 x 1150 x 1535*	3000 x 1150 x 2135*
Genset weight (kg)	840	930	950	1260	1280	1350

Engine Specifications						
Make	Mahindra					
Model	3385 TCIGM C2	3445 TCIGM C2	4575 TCIGM C2	4725 GMAC2	4905 GMAC2	41035 GM C2
Rated Power at 100% Load (HP)	34.5	40	51.8	65.4	81.8	93.7
Aspiration	TCI	TCI	TCI	TCI	TCI	TCI
No. of cylinders	3	3	4	4	4	4
Bore x Stroke (mm)	89 x 102	89 x 110	89 x 110	94 x 115	96 x 122	96 x 122
Displacement (cc)	1892	2048	2731	3192	3532	3532
Lube oil specification	SAE15W40 CI4					
Total lube oil system capacity (liter)	7	7	10.5	10	10	10
Lube oil consumption (lit./hr) [§]	0.15% of Fuel Consumption				0.1% of Fuel Consumption	
Lube oil change period (hrs.)	300 hrs. (Oil Change)					
Radiator coolant capacity (liters)	9.5	9.5	9.5	12	15	19

Alternator Specifications						
Make	Leroy Somer					
Enclosure Type	IP23	IP23	IP23	IP23	IP23	IP23
Voltage regulation	±1%	±1%	±1%	±1%	±1%	±1%
Class of insulation	Class H	Class H	Class H	Class H	Class H	Class H
Maximum Unbalanced Load across Phases	25%	25%	25 %	25%	25%	25%

Notes:
Above specifications are subject to change without prior notice due to continuous product improvements
All engines & alternators conform to respective IS standards
All the genset specifications conform to ISO 8528 standard
*Height without silencer
Fuel - High Speed Diesel (HSD IS 1460 : 2005)
^ Considering 0.845 specific gravity of diesel, 5% tolerance
\$ Considering 0.89 specific gravity of oil
All specifications are at standard NTP operating conditions



Mahindra & Mahindra Ltd.
Powerol Business, Powerol Building,
Gate No. 2, Akurli Road, Kandivali (E),
Mumbai - 400 101, India.



+91 22 3313 3959/ 3825



poweroldg@mahindra.com



mahindrapowerol.com